

► +44 (0)161 928 6221 info@hydratron.co.uk



TECHNICAL DATA SHEET

| PRODUCT | HPU-HP100-N*/options |
|---------|---|
| SERIES | HPU-HP Hand operated hydraulic pumps for pressure testing purposes, suitable for either oil or water services. |



FEATURES

- Infinitely variable output pressure and flow
- Holds static pressure without generating heat or consuming power.
- Standard models are suitable for oil or water applications
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

PERFORMANCE DATA

| Max Rated Output Pressure | 10,000psi (690bar) |
|---------------------------|-----------------------|
| Output Per Cycle | 0.30 in³ (5cc/ml) |
| Tank Capacity | 1 Gallon (4.5 litres) |

SEAL OPTIONS (N*)

| N* (standard) | Nitrile (Buna-N) Main Seal and Check Valve Seals |
|---------------|--|
| EPDM | EPDM Main Seal and Check Valve Seals |

CONSTRUCTION

| Frame and Tank | Stainless Steel |
|----------------|---|
| Body | Stainless Steel |
| Piston | Stainless Steel + Chrome Finish |
| Check Valves | Stainless Steel (Seals as per Selected Seal Option) |
| Handle | Stainless Steel Handle – Rubber Grip (23 1/2" 600mm LG) |





Pag. 2 of 2

CONNECTIONS

| Hydraulic Outlet | 3/8" NPT(F) |
|------------------|-------------|
| Net Weight | 20kg (44lb) |

COMMON OPTIONS (BUT NOT LIMITED TO)

| / B | Recorder connection |
|-----|---------------------|
| / 2 | Isolation valve |

GENERAL LAYOUT DRAWING

Model: HPU-HP100-N





