

+44 (0)161 928 6221 info@hydratron.co.uk

# **TECHNICAL DATA SHEET**

| PRODUCT | PU-HP10-N*/options  |  |
|---------|---|--|
| SERIES  | НР  |  |
|         | Hand operated hydraulic pumps for pressure testing purposes, suitable for either oil or water services. |  |

## **FEATURES**

- Infinitely variable output pressure and flow
- Holds static pressure without generating heat or consuming power.
- Standard models are suitable for oil or water applications
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

| PER | EO | <b>DM</b> | ΛN     | CE  | DA                 | TA           |
|-----|----|-----------|--------|-----|--------------------|--------------|
|     |    | LAIVE     | $\neg$ | CL. | $\boldsymbol{\nu}$ | $\mathbf{n}$ |

| Max Rated Output Pressure | 1,000psi (69bar)            |
|---------------------------|-----------------------------|
| Output Per Cycle          | 3 in <sup>3</sup> (49cc/ml) |

## **SEAL OPTIONS (N\*)**

| N* (standard) | Nitrile (Buna-N) Main Seal and Check Valve Seals |
|---------------|--|
| EPDM          | EPDM Main Seal and Check Valve Seals             |

#### **CONSTRUCTION**

| Body         | Stainless Steel   |
|--------------|---|
| Piston       | Stainless Steel   |
| Check Valves | Stainless Steel (Seals as per Selected Seal Option)     |
| Handle       | Stainless Steel Handle – Rubber Grip (23 1/2" 600mm LG) |





Model: PU-HP10-N



Pag. 2 of 2

## **CONNECTIONS**

| Hydraulic Inlet  | 1/4" NPT(F) |
|------------------|-------------|
| Hydraulic Outlet | 1/4" NPT(F) |
| Net Weight       | 9kg (20lb)  |

## **COMMON OPTIONS (BUT NOT LIMITED TO)**

| /1  | Pressure release valve |
|-----|------------------------|
| / 2 | Isolation valve        |

## **GENERAL LAYOUT DRAWING**





