

← +44 (0)161 928 6221 info@hydratron.co.uk

# **TECHNICAL DATA SHEET**

HYPS-AZ-2-60H-N\*/\*\*options **PRODUCT SERIES HYPS-AZ-2 Single Acting** Air operated, hydraulic power pack for pressure testing, chemical injection and hydraulic power.



#### **FEATURES**

- Infinitely variable output pressure and flow
- Holds static pressure without generating heat or consuming power
- Standard models are suitable for oil or water applications
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing

Basic Models are ATEX Certified in accordance with 2014/34/EU. Note: addition of options may affect ATEX rating.

#### **PERFORMANCE DATA**

Max Rated Output Pressure	6,000psi (414bar)
Output Per Cycle	1.5 in <sup>3</sup> (24.6cc)
Max Flow	378 in <sup>3</sup> /min (6.2 litre/min)
Max Air Supply Pressure	100psi (7bar)
Ratio	60 : 1
Air Consumption	56 scfm (1,586 NI/min)
Tank Capacity	2.5 Gallons (11.4 litres)

### **SEAL OPTIONS (N\*)**

N*	(Standard) Nitrile (Buna-N) Main Seal and Check Valve Seals
V	Viton (FKM) Main Seal and Check Valve Seals
С	Chemraz (FFKM) Main Seal and Check Valve Seals







## **CONSTRUCTION**

Frame and Tank	Stainless Steel
Air Motor	Anodised Aluminium / Wound Composite / Nitrile (Buna-N)
Hydraulic Cylinder	Stainless Steel
Piston	Stainless Steel + Chrome Finish
Outlet Port	Stainless Steel

# **CONNECTIONS**

Hydraulic Outlet	3/8" MP(F)
Air Inlet	1/2" BSPP(F)
Net Weight	30kg (66lb)

# **COMMON OPTIONS (BUT NOT LIMITED TO)**


/ D	External fluid supply via bulkhead (no tank fitted)
/ T	Stainless steel tank fitted
/ Tx	Stainless steel tank fitted with external fluid supply port
/ F	Panel mount digital stroke counter (non ATEX)
/ G	Panel mount pneumatic stroke counter
/1	Test isolation valve fitted
/0	Single pen chart recorder complete with recorder isolation valve
/ W	Fitted with wheels
/ R	Relief valve fitted and set in test line





Pag. 3 of 3

#### **GENERAL LAYOUT DRAWING**



### **HYDRAULIC PRESSURE STATIC / STALL CONDITIONS**

AIR PRESSURE	HYDRAULIC PRESSURE
20psi (1.4bar)	1,050psi (72.4bar)
40psi (2.8bar)	2,275psi (157bar)
60psi (4bar)	3,500psi (241bar)
80psi (5.5bar)	4,650psi (321bar)
100psi (7bar)	6,000psi (414bar)

#### **FLOW CURVE** AZ-2-60 - Ratio 60:1

