

+44 (0)161 928 6221 info@hydratron.co.uk



TECHNICAL DATA SHEET

PU-DA66/4-N*-L1**/options PRODUCT SERIES **DA Double Acting** Air operated, high flow, double acting hydraulic pumps for pressure testing, chemical injection and hydraulic power.



FEATURES

- Infinitely variable output pressure and flow
- Holds static pressure without generating heat or consuming power
- Standard models are suitable for oil or water applications
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

PERFORMANCE DATA

Max Rated Output Pressure	6,625psi (457bar)
Output Per Cycle	8.0 in³ (131cc)
Max Flow	1,153 in³/min (19 litre/min)
Max Air Supply Pressure	100psi (7bar)
Ratio	66 : 1
Air Consumption	120 scfm (3,400 NI/min)

SEAL OPTIONS (N*)

N* (standard)	Nitrile (Buna-N) Main Seal and Check Valve Seals
V	Viton (FKM) Main Seal and Check Valve Seals
С	Chemraz (FFKM) Main Seal and Check Valve Seals

CONSTRUCTION

Air Motor	Anodised Aluminium / Nitrile (Buna-N) Seals







Pag. 2 of 3

Hydraulic Cylinder	Aluminium Bronze
Piston	Stainless Steel + Corrosion Resistant Chrome Finish
Check Valves	Stainless Steel (Seals as per Selected Seal Option)
Pilot Air Valves	Brass / Stainless Steel Internals / Nitrile (Buna-N) Seals / Stainless Steel Pipework
L1** (standard)	Plated Steel Silencer
L2** (optional)	Stainless Steel Silencer


CONNECTIONS

Hydraulic Inlet	1/2" NPT(F)
Hydraulic Outlet	1/2" NPT(F)
Air Inlet	3/4" NPT(F)
Pilot Air Supply	1/8" BSPP(F)
Net Weight	40kg (88lb)

COMMON OPTIONS (BUT NOT LIMITED TO)

/ A	ATEX (94/9/EC) II 2GD c T5
/ F	Panel mount digital stroke counter (non ATEX)
/ G	Panel mount pneumatic stroke counter

GENERAL LAYOUT DRAWING










Pag. 3 of 3

HYDRAULIC PRESSURE STATIC / STALL CONDITIONS

AIR PRESSURE	HYDRAULIC PRESSURE
20psi (1.4bar)	1,325psi (91bar)
40psi (2.8bar)	2,650psi (183bar)
60psi (4bar)	3,975psi (274bar)
80psi (5.5bar)	5,300psi (366bar)
100psi (7bar)	6,625psi (457bar)

DA66 - Ratio 66:1 **FLOW CURVE**



-100 Psi Air Drive 75 Psi Air Drive -50 Psi Air Drive



