


TECHNICAL DATA SHEET

PRODUCT	PU-GBS15-L**/options	
SERIES	Single Acting Air operated, high flow gas booster compressors offer a flexible and efficient source for delivering high pressure gases.	

FEATURES

- Infinitely variable output pressure and flow
- Will hold static pressure without generating heat or consuming power
- Standard models are suitable for various gases
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

PERFORMANCE DATA

Max Rated Output Pressure	1,500psi (103bar)
Displacement Per Cycle	6.0 in ³ (98.3cc)
Max Flow	9.72 scfm (275 NI/min)
Max Air Supply Pressure	100psi (7bar)
Ratio	12 : 1
Air Consumption	56 scfm (1,586 NI/min)
Supply Pressure to Achieve Max Output Pressure	125psi (8.6bar)
Actual Output Pressure (Stall Condition)	15 x (Air drive pressure)

SEAL MATERIAL

Main Seals	MoS2
Check Valve Seals	Viton

CONSTRUCTION

Air Motor	Anodised Aluminium / Wound Composite / Nitrile (Buna-N) Seals
Gas Cylinder	17-4PH + Chrome Finish
Piston	Aluminium Bronze
Check Valves	Stainless Steel
L1** (standard)	Copper / Brass, Pipework / Fittings & Plated Steel Silencer
L2** (optional)	Stainless Steel Pipework, Fittings & Silencer

CONNECTIONS

Gas Inlet	3/8" NPT(F)
Gas Outlet	3/8" NPT(F)
Net Weight	16kg (35lb)

COMMON OPTIONS (BUT NOT LIMITED TO)

/ A	ATEX (94/9/EC) II 2GD c T5
/ F	Panel mount digital stroke counter (non ATEX)
/ G	Panel mount pneumatic stroke counter

GENERAL LAYOUT DRAWING

Model: **PU-GBS15**

